

CONTENT OF CMC SAMPLE-KIT VITROPERM®

I _N A	Design	U _N	L _N 10 kHz	L _N 100 kHz	R _{Cu} typ. mΩ	Z 100 kHz Ω	f _R typ. MHz	I _{cm} 10 kHz mA	Dimensions			Part Number
		OVCat III/II V							L	B	H	
CMCs for 1-phase Applications												
4	upright	300/600	2x10.8	2x2.5	27.5	2320	1.2	12	22	12	25	T60405-R6131-X204
4.5	upright	300/600	2x28.3	2x6.6	36	6500	0.4	18	27	17	29	T60405-R6161-X504
6	upright	300/600	2x29.1	2x6.7	37.6	8500	0.25	14	35	21	37	T60405-R6166-X206
8	upright	300/600	2x16.4	2x3.7	19.1	4200	0.5	20	35	21	36.5	T60405-R6166-X208
10	low profile	300/600	2x11.4	2x2.6	12.2	3200	0.7	16	35	35	23	T60405-R6123-X210
12	low profile	300/600	2x11.4	2x2.6	8.8	2950	0.7	22	35	35	25	T60405-R6123-X213
16	low profile	300/600	2x12.9	2x3.1	5.7	3000	3.0	37	40	40	24	T60405-R6123-X616
16	upright	300/600	2x6	2x1.5	4.6	1600	1.0	35	38	21	38	T60405-R6166-X033
20	low profile	300/600	2x1.8	2x0.4	3.2	500	11.5	40	35	35	23.5	T60405-R6123-X220
20	low profile	300/600	2x6.6	2x1.6	2.9	1470	5.7	35	43	43	24	T60405-R6123-X221
25	low profile	300/600	2x4.2	2x1	1.9	970	7.1	50	42.5	42.5	25	T60405-R6123-X226
25	low profile	600/1000	2x12	2x2.8	3.5	2900	2.4	55	52	52	32	T60405-R6123-X227
25	upright	300/600	2x4.2	2x1	1.9	970	4.9	50	42	27	40	T60405-R6128-X225
30	upright	600/1000	2x3.9	2x0.9	2.3	900	4.0	65	51	27	50	T60405-R6128-X031
48	low profile	600/1000	2x2.5	2x0.6	0.75	660	6.7	110	52	52	32	T60405-R6123-X248
3-phase Chokes for 3-phase Applications												
10	low profile	600/1000	3x13.9	3x3.2	14	3500	1.5	30	51	51	32	T60405-S6123-X310
11	low profile	600/1000	3x10.6	3x2.5	8.5	2600	0.8	40	42	42	32	T60405-S6123-X308
12	low profile	600/1000	3x5.7	3x3.7	11.8	2650	0.48	150	51	51	32	T60405-S6123-X312
16	low profile	600/1000	3x9.4	3x2.2	5.9	2400	1.45	35	51.5	51.5	34	T60405-S6123-X317
20	low profile	600/1000	3x10.6	3x2.4	4.1	2650	0.9	60	59	59	33	T60405-S6123-X320
25	low profile	600/1000	3x4.9	3x1.1	2.1	1150	2	60	51.5	51.5	32	T60405-S6123-X326
32	low profile	600/1000	3x1.2	3x0.8	1.4	600	4.9	480	59	59	33	T60405-S6123-X332
40	low profile	600/1000	3x2.5	3x0.6	1.2	600	4.7	100	52	52	33	T60405-S6123-X140
4-fold Chokes												
20	low profile	600/1000	4x3.6	4x0.8	2.75	860	3.4	90	51.5	51.5	33	T60405-S6123-X401

Further information about our CMCs is available in our brochure PKB-EMC Edition 2010 or on our website.

VACUUMSCHMELZE GMBH & CO. KG

Grüner Weg 37 • D 63450 Hanau / Germany

Phone +49 6181 380 • info@vacuumschmelze.com • www.vacuumschmelze.com

info@vacuumschmelze.com • www.vacuumschmelze.com

ADVANCED MAGNETIC SOLUTIONS

VAC®
VACUUMSCHMELZE